

CERTI-VEX[®] PC RELEASE AIM

PRECAST FORM RELEASE AIM • LOW VOC

DESCRIPTION

CERTI-VEX PC RELEASE AIM is chemically active oil based low VOC form release engineered for premium release of metal forms. The product contains special high quality hydro-treated oil and surface active release agents which inhibit concrete adhesion to the form yielding a smooth, clean and void free surface. The product includes a special rust inhibitor to minimize rust formation on metal forms.

Certi-Vex PC Release AIM minimizes concrete build up extending the forms useful life while reducing cleaning and maintenance costs.

When properly applied Certi-Vex PC Release AIM will not interfere with subsequent coatings or treatments of formed concrete.

BENEFITS

- Yields smooth residue free surfaces
- Reduces form preparation between uses
- Reduces spalling, bug holes and surface voids
- Non-staining
- Fast drying
- Forms strip easily and cleanly
- Low VOC
- Minimizes rust formation on steel forms between pours
- Low odor

RECOMMENDED FOR

- Architectural concrete
- Pre-cast, pre-stressed & steamed cured concrete
- General forming applications

USE ON THESE TYPES OF FORM FACE MATERIALS

- Wood
- Aluminum
- Steel
- Fiberglass
- Medium Density Overlay (MDO) Plywood

SPECIFICATIONS/COMPLIANCE

- VOC <250 grams/liter or < 2.08 #/gal
- Meets
 - US EPA AIM – Form Release Compounds
 - OTC – Form Release Compounds
 - LADCO/MRPO – Form Release Compounds
 - CEPA/EC – Form Release Compounds
 - CARB – Form Release Compounds
 - SCAQMD – Rule 1113 – Form Release Compounds
- Federal Unified Facilities Guide Specification (UFGS) for Precast Architectural Concrete
- CSI reference: 03 11 00 – Concrete Forming

APPLICATION

- Apply to clean, reasonably dry forms.
- Remove previous build up of concrete, rust and dirt with **Certi-Vex Concrete Remover** and **Certi-Vex Rust Remover**.
- Repair any holes or fractures from previous use before applying.
- Certi-Vex PC Release AIM is ready to use directly from its container, do not dilute.
- Apply by; brush, roller, or spray to forms immediately before pouring concrete.
- Keep off reinforcing steel, prestressed cables and any other embedment's when forms and steel are already in place. An alternative is to apply Certi-Vex PC Release AIM to forms just prior to erection of rebar steel.
- It is recommended that forms be treated with Certi-Vex PC Release AIM between each pour and before long periods of idleness or storage.
- Coat Uniformly - Leave No Gaps.

COVERAGE/ESTIMATING

Coverage rates below are estimates only and will depend on porosity, texture and form material. Conduct a test application to verify the proper application rate for your use.

- Typical application rate on smooth-faced forms is 800-1,200 sq.ft. /gal (20-30 m²/L) sf/gal.
- Typical application rate on textured forms is 600-800 sq.ft. /gal (15-20 m²/L) sf/gal.

SPECIAL NOTES

- New forms should be seasoned prior to the application of Certi-Vex PC Release AIM.
- Residual concrete dust can be wiped off with a rag or water washed to a clean surface.
- Do not use as a bond breaker for concrete on concrete.
- Manufacturers of coatings or treatments should be consulted for special application requirements of their product.
- Certi-Vex PC Release AIM can be effective for up to three weeks before concrete is poured.
- It is also recommended that forms be treated with Certi-Vex PC Release AIM between each pour and before long periods of idleness or storage.
- Do not apply form release treatment when surface temperatures are below 20° F (-7° C).
- Do not over apply. Excess should be promptly removed.
- Certi-Vex PC Release AIM is ready to use directly from its container, do not dilute.
- For use by experienced contractors.
- Shelf Life: If properly stored in its original sealed container, three years from date of manufacture. Rotate your stock.
- Storage/ Handling: Store in tightly sealed original factory container. Keep from freezing and exposure to moisture. Store at room temperature prior to use. Special care should be taken to keep dirt, water and contaminants away from the opening of containers.
- Delivery: Deliver materials to site in manufacturer's original, unopened containers and packaging, with labels clearly identifying product name and manufacturer.
- Proper application of Vexcon material is the responsibility of the installer or user. Telephone consultation and/or field visits by Vexcon personnel are for the sole purpose of making technical recommendations only, and not for providing quality control or supervision on location.

PHYSICAL PROPERTIES

- Color Light Brown-Clear Oil Based Liquid
- Wt/Gal 7.15 +/- 0.1
- Acid Number None
- Carrier Naphthenic Petroleum Oil

PACKAGING

Certi-Vex PC Release AIM is available in 275 gallon totes, 55-gallon drums, and 5-gallon pails. Contact Vexcon to discuss your customized packaging requirements.

HEALTH AND SAFETY

- Use only with adequate ventilation.
- If swallowed, do not induce vomiting.
- Use of gloves, goggles and other protective clothing is advised when using this product.

Vexcon SDS FR135AIM is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this Vexcon product it is advisable to obtain a copy of the SDS from your distributor or available at vexcon.com.

CONTACT US @

Additional product information, technical assistance and customer service is available by contacting Vexcon Chemicals directly, or our distributors.

- vexcon.com
- techservice@vexcon.com
- customerservice@vexcon.com
- sales@vexcon.com
- Voice: 888.839.2661
- Fax: 215.332.9997

WARRANTY

LIMITED WARRANTY: Vexcon warrants for a period of one (1) year from the date of manufacture that the goods supplied hereunder shall be of its standard quality and free of defects, and conforms to (a) Vexcon's published specifications in force on the date of acceptance by Vexcon of the order and (b) the sample which has been made available for testing by buyer prior to sale. Any claim under this warranty must be made in writing to Vexcon Chemicals within sixty (60) days after such non-conformity is first discovered. As the EXCLUSIVE REMEDY for any breach of this Limited Warranty, Vexcon at its option shall replace nonconforming goods or refund the purchase price. Since methods of use and application are beyond Vexcon's control, this Limited Warranty IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THOSE CONCERNING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THIS LIMITED WARRANTY IS ALSO IN LIEU OF ANY OTHER POSSIBLE LIABILITIES OF VEXCON, WHETHER ALLEGED TO ARISE BY AGREEMENT OR BY OPERATION OF LAW, RESPECTING THE SALE, APPLICATION, USE OR FUNCTION OF VEXCON'S PRODUCTS, INCLUDING BUT NOT LIMITED TO CLAIMS OF NEGLIGENCE, GROSS NEGLIGENCE, MISUSE, STORAGE DAMAGE, MISAPPLICATION, ACCIDENT, STRICT LIABILITY OR ANY OTHER TORT. No person is authorized by Vexcon to assume for it any other liability of any kind in connection with the sale or use of products manufactured and sold by it, and there are no oral agreements or warranties collateral to or affecting any sale or use. All of the foregoing arises under the substantive law of Pennsylvania without regard to principles of conflicts of laws.

LIMITATION OF LIABILITY: IN ALL EVENTS VEXCON'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF PURCHASED PRODUCTS. IN NO EVENT SHALL VEXCON BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE, REAL OR PERSONAL, ATTRIBUTED TO ITS PRODUCTS, NOR FOR ANY EXCAVATION, REMOVAL, REAPPLICATION, DOWN TIMES, CLEANUP, LOSS OF USE, LOSS OF OPPORTUNITY, LOSS OF MARKET VALUE, LOSS OF RENTAL VALUE OR FOR ANY LOSS OF PROFITS OR OTHER SPECIAL, INCIDENTAL, RESULTING, CONSEQUENTIAL OR EXEMPLARY DAMAGES.