

HAZARD RATING
 4=EXTREME
 3=HIGH
 2=MODERATE
 1=SLIGHT
 0=INSIGNIFICANT

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0


SAFETY DATA SHEET
 VEXCON NO. FR202

CERTI-VEX CONCRETE REMOVER

SECTION I - GENERAL INFORMATION

PRODUCT IDENTIFICATION:	
CERTI-VEX CONCRETE REMOVER	
VOC CONTENT:	0 GRAMS/LITER
CATEGORY:	NON-REGULATED
COMMON NAME:	OIL BASED CONCRETE SOFTENER
MANUFACTURER:	VEXCON CHEMICALS, INC
ADDRESS	7240 STATE RD, PHILADELPHIA, PA 19135
EMERGENCY NO:	800.858.2828 (PolySat Inc)
TELEPHONE NO:	215.332.7709 (Vexcon)
CHEMTREC NO:	800.424.9300 (CCN# 23822)
PREPARED:	AUGUST 2008
UPDATED:	SEPTEMBER 2016
PREPARED BY:	DARRY F. MANUEL , PRESIDENT

SECTION II - HAZARD IDENTIFICATION

DOT SHIPPING NAME: UN ID NUMBER / SHIPPING NAME / HAZARD CLASS / PKG GROUP IN CONTAINERS LESS THAN AND GREATER 119 GALS: IN ALL MODES OF TRANSPORTATION (NON-REGULATED)
HEALTH AND SAFETY: USE ONLY WITH ADEQUATE VENTILATION: IF SWALLOWED, DO NOT INDUCE VOMITING: USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE EQUIPMENT IS ADVISED WHEN HANDLING THIS PRODUCT: ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL: USE OF RESPIRATORS IS ADVISED WHEN USING PRODUCT IN CONFINED AREA.


SECTION III HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENTS	CAS NO.	%	HAZARD DATA	UN#
PETROLEUM HYDRO-TREATED OIL	64742-53-6	70-90%	OSHA PEL TWA: 5 mg/m3 (OIL MIST)	NONE
Release and Wetting Agent	NA	20-30%	NA	NONE

SECTION IV FIRST AID MEASURES

HEALTH HAZARD DATA HAZARD CLASSIFICATION
 BASIS FOR CLASSIFICATION SOURCE

ROUTES OF EXPOSURE:	
INHALATION:	THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES. DIZZINESS, LIGHTHEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. VAPOR INHALATION CAN CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA OR HEADACHE.
SKIN CONTACT:	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT.
SKIN ABSORPTION:	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT.
EYE CONTACT:	THIS PRODUCT MAY BE AN EYE IRRITANT.
INGESTION / INHALATION	CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING. SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.
EFFECTS OF OVEREXPOSURE:	ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES.
ACUTE OVEREXPOSURE:	ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES. PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEFAT THE SKIN POSSIBLY CAUSING DERMATITIS.
EMERGENCY AND FIRST AID PROCEDURES:	
EYES:	FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION. CONSULT A PHYSICIAN.
SKIN:	WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.
INHALATION:	MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION. NOTE: THIS MATERIAL RELEASES ETHYL ALCOHOL UPON HYDROLYSIS. ETHYL ALCOHOL CAUSES OPTIC NEUROPATHY, METABOLIC ACIDOSIS AND RESPIRATORY DEPRESSION. SIGNS AND SYMPTOMS OF OVEREXPOSURE INCLUDE HEADACHE, BLURRED VISION, CONSTRICTED VISUAL FIELDS, SHORTNESS OF BREATH, DIZZINESS AND VERTIGO.

SECTION V FIREFIGHTING MEASURES

EXTINGUISHING MEDIA:	EXCLUDE AIR. FIRES INVOLVING THIS PRODUCT MAY BE CONTROLLED BY HALON FOAM, CARBON DIOXIDE, DRY CHEMICALS OR WATER SPRAY. WATER MAY BE USED TO REDUCE THE RATE OF BURNING AND FOR COOLING PURPOSES. AVOID SPRAYING WATER DIRECTLY INTO STORAGE CONTAINERS DUE TO DANGER OF BOIL OVER.
GENERAL HAZARD:	FLAMMABLE OR COMBUSTIBLE LIQUID - CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC DISCHARGE - MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF.
ELECTRO-STATIC ACCUMULATION HAZARD:	USE PROPER GROUNDING
UNUSUAL FIRE AND EXPLOSION HAZARD:	PRODUCT WILL BURN IF TEMPERATURE EXCEEDS BOILING POINT. THIS PRODUCT IS EXTREMELY FLAMMABLE AND EXPLOSIVE UNDER NORMAL CONDITIONS IN THE PRESENCE OF FLAME OR SPARK SOURCE. FLAMMABLE VAPORS MAY ACCUMULATE IN THE CONTAINER HEADSPACE ON FORMATION OF HYDROLYSIS BY-PRODUCTS. IF STORAGE CONTAINERS ARE EXPOSED TO EXCESSIVE HEAT, OVER PRESSURIZATION OF THE CONTAINERS CAN RESULT. VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR THROUGH VENTILATION SYSTEM CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER SOURCES OF IGNITION.
SPECIAL FIRE FIGHTING PROCEDURES	THE USE OF SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE SHOULD BE PROVIDED FOR FIRE FIGHTERS IN BUILDINGS OR CONFINED AREAS WHERE THIS PRODUCT IS STORED. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY IN ORDER TO PREVENT PRESSURE BUILD UP. USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES AND TO PROTECT PERSONNEL. ISOLATE "FUEL" SUPPLY FROM FIRE. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES.

SECTION VI ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:
LAND SPILL: ELIMINATE SOURCES OF IGNITION. PREVENT ADDITIONAL DISCHARGE OF MATERIAL; IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS, IMPLEMENT CLEANUP PROCEDURES. FOR LARGE SPILL, IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. ALSO, IF THIS PRODUCT IS SUBJECT TO CERCLA REPORTING NOTIFY THE NATIONAL RESPONSE CENTER. PREVENT LIQUID FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. RECOVER BY PUMPING (USE AN EXPLOSION PROOF OR HAND PUMP) OR WITH A SUITABLE ABSORBENT. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.
WATER SPILL: REMOVE FROM SURFACE BY SKIMMING OR WITH SUITABLE ABSORBENTS. IF ALLOWED BY LOCAL AUTHORITIES AND ENVIRONMENTAL AGENCIES, SINKING AND/OR SUITABLE

DISPERSANTS MAY BE USED IN NON-CONFINED WATERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

SECTION VII HANDLING AND STORAGE

PRECAUTIONARY STATEMENTS: PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE REUSE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

FIRE FIGHTING: WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIUM BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS.

OTHER HANDLING AND STORAGE REQUIREMENTS: STORE AND USE IN WELL VENTILATED AREA, EQUIVALENT TO FRESH AIR. KEEP CONTAINERS COOL, DRY, AND AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREAS WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, SOURCES OF IGNITION, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

SECTION VIII EXPOSURE CONTROLS / PERSONAL PROTECTION

VENTILATION REQUIREMENTS: LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

RESPIRATORY (SPECIFY IN DETAIL): THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIR-PACK. CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE. FULL FACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

EYES: CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

GLOVES: THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS. IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

OTHER CLOTHING AND EQUIPMENT: TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS AND HELMETS (HEAD COVER) ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

SECTION IX PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: (760mmHg) 500-700° F (260-370°C)	MELTING/FREEZING POINT: -65°F (-55°C)
VAPOR PRESSURE: NA	VAPOR DENSITY (AIR=1): .5
SOLUBILITY IN H2O % BY WT: Nil	% VOLATILES BY VOL: Nil LVP-VOC
EVAPORATION RATE (BuAc=1): NA	SPECIFIC GRAVITY (H2O=1) 0.88
pH (AS IS): N/A	pH (1% SOLN): N/A
APPEARANCE AND ODOR:	CLEAR GREN LIQUID WITH PETROLEUM ODOR
FLASH POINT: (TEST METHOD)	290°F/143°C (Does not sustain burning per ASTM D-4206)
AUTOIGNITION TEMP:	>600°F (315°C)
FLAMMABLE LIMITS IN AIR, % BY VOL:	LOWER: ND UPPER: ND

SECTION X STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY:	THIS PRODUCT IS STABLE.
INCOMPATIBILITY:	THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES, AND SELECTED AMINES.
HAZARDOUS DECOMPOSITION PRODUCTS:	THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE, AND UNIDENTIFIED ORGANICS.
CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:	N/A WILL NOT OCCUR

SECTION XI TOXICOLOGICAL INFORMATION

INFORMATION ON LIKELY ROUTES OF EXPOSURE	
INGESTION	MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS
INHALATION	MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS
SKIN CONTACT	DUE TO LACK OF DATA THE CLASSIFICATION IS NOT POSSIBLE
EYE CONTACT	DUE TO LACK OF DATA THE CLASSIFICATION IS NOT POSSIBLE
SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS.	
INFORMATION ON TOXICOLOGICAL EFFECTS	
ACUTE TOXICITY	MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS
SKIN CORROSION/IRRITATION	DUE TO LACK OF DATA THE CLASSIFICATION IS NOT POSSIBLE
SERIOUS EYE DAMAGE	DUE TO LACK OF DATA THE CLASSIFICATION IS NOT POSSIBLE
RESPIRATORY OR SKIN SENSITIZATION	
RESPIRATORY SENSITIZATION	DUE TO LACK OF DATA THE CLASSIFICATION IS NOT POSSIBLE
SKIN SENSITIZATION	DUE TO LACK OF DATA THE CLASSIFICATION IS NOT POSSIBLE
GERM CELL MUTAGENICITY	NO DATA AVAILABLE TO INDICATE PRODUCT OR ANY COMPONENTS PRESENT AT GREATER THAN 0.1% ARE MUTAGENIC OR GENOTOXIC.
CARCINOGENICITY	BASED ON AVAILABLE DATA, THE CLASSIFICATION CRITERIA ARE NOT MET.
REPRODUCTIVE TOXICITY	DUE TO LACK OF DATA THE CLASSIFICATION IS NOT POSSIBLE.
SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE	DUE TO LACK OF DATA THE CLASSIFICATION IS NOT POSSIBLE
SPECIFIC TARGET ORGAN TOXICITY – REPEATED EXPOSURE	DUE TO LACK OF DATA THE CLASSIFICATION IS NOT POSSIBLE
ASPIRATION HAZARD	MAY BE FATAL IF SWALLOWED AND ENTER AIRWAYS
CHRONIC EFFECTS	PROLONGED INHALATION MAY BE HARMFUL

SECTION XII ECOLOGICAL INFORMATION

ECOTOXICITY	NOT EXPECTED TO BE HARMFUL TO AQUATIC ORGANISMS.
PERSISTENCE AND DEGRADABILITY	NO DATA IS AVAILABLE ON THE DEGRADABILITY OF THE PRODUCT
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE FOR THIS PRODUCT
MOBILITY IN SOIL	NOT AVAILABLE
OTHER ADVERSE EFFECTS	NO OTHER ADVERSE ENVIRONMENTAL EFFECTS (E.G. OZONE DEPLETION, PHOTOCHEMICAL OZONE CREATION POTENTIAL, ENDOCRINE DISRUPTION, GLOBAL WARMING POTENTIAL) ARE EXPECTED FROM THIS COMPONENT.

SECTION XIII DISPOSAL CONSIDERATIONS

AQUATIC TOXICITY (E.G. 96 HR. TLM): Do not discharge this product into public waters or waterways unless authorized by a National Pollution Discharge Elimination System (NPDES) permit issued by the Environmental Protection Agency (EPA).
WASTE DISPOSAL METHOD: IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, FEDERAL, STATE, AND LOCAL REGULATIONS. TREATMENT, TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA FEDERAL, STATE, AND LOCAL REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT (RCRA, 40 CFR 261). TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LAND FILL SITES ARE AVAILABLE.

SECTION XIV TRANSPORTATION INFORMATION

Governing Body	Mode	UN Number	Proper Shipping Name	Hazard Class	Packing Group
DOT	GROUND	NON-REGULATED	NON REGULATED	NON REGULATED	NA
IATA	AIR	NON REGULATED	NON REGULATED	NON REGULATED	NA
IMDG	OCEAN	NON REGULATED	NON REGULATED	NON REGULATED	NA
MARINE POLLUTANT:	THIS PRODUCT DOES NOT CONTAIN A MATERIAL ON THE MARINE POLLUTANTS TABLE (HMT 172.101 APPENDIX B)				

SECTION XV REGULATORY INFORMATION

CERCLA: IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 1-800-424-8802 or 202-426-2675. NONE
SARA TITLE III: UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES: IMMEDIATE HEALTH HAZARD
ADDITIONAL REGULATORY CONCERNS: (FEDERAL, FDA, USDA, CPSC, STATE, OTHER)
FEDERAL / FDA / USDA:
MARINE POLLUTANTS: NO. THIS PRODUCT DOES NOT CONTAIN A MATERIAL ON THE MARINE POLLUTANTS TABLE (HMT 172.101 Appendix B).
CERCLA / RQ NONE ESTABLISHED. THIS PRODUCT DOES NOT CONTAIN A MATERIAL ON THE RQ TABLE (HMT 172.101 Appendix A):
TSCA: IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

SECTION XVI OTHER INFORMATION

PREPARED BY	DARRYL MANUEL / PRESIDENT
COMPANY:	VEXCON CHEMICALS, INC.
ADDRESS:	7240 STATE RD., PHILA., PA 19135 USA
THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESSED OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN.	

HMIS HAZARD RATINGS:			KEY 4 -- SEVERE
THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS			
CERTI-VEX CONCRETE REMOVER	NPC A- HMIS	NFP A 704	3 -- SERIOUS
HEALTH	1	1	2 -- MODERATE
FLAMMABILITY	1	1	1 -- SLIGHT
REACTIVITY	0	0	0 -- MINIMAL